

CBF SERIES



CM POWER
LEADS
THE WAY



Crusher bucket designed for crushing inert material directly on site. Suitable for any type of construction site, it can work in the most difficult conditions while maintaining performance.

STRENGTHS

- Body built 90% in Hardox® 450
- Crushing plates made of a 18% manganese cast
- Single pressure relief valve and speed regulation
- Centralized greasing
- Output size adjustment from 20 to 140 mm
- Easy and uncomplicated maintenance



OPTIONAL

- Excavation teeth
- Magnet + Control panel kit
- Dust suppression kit
- Pre-arrangement for backhoe / wheel loader / telescopic handler
- Hour meter
- Tachometer

DATA SHEET		CBF 60	CBF 70	CBF 90	CBF 120
Excavator	ton	≥10 <17	≥15 <25	≥20 <32	≥30 <45
Mouth size	w x H mm	610 x 500	710 x 550	910 x 550	1210 x 550
Weight	Kg	1831	2436	3543	5052
Load capacity	m³	0,58	0,70	0,90	1,20
Pressure	bar	>220	>220	>220	>220
Oil flow	l/min	>120 <180	>150 <200	>160 <220	>180 <250
Opening	mm	20/140	20/140	20/140	20/140
Dimensions	w x d x H mm	1000 x 1800 x H 1200	1100 x 2000 x H 1250	1300 x 2100 x H 1350	1600 x 2100 x H 1350

CRUSHING SIZE FROM 20 UP TO 20/140 mm STEP.
Weights and dimensions could vary without notice. Weight does not include the coupler.



Canalization / Subsoil



Demolitions



Construction industry



Tunnel / Closed space



Agricultural / Forest maintenance



Recycling



Quarries / Mines



Streets

