
MB-G450







ACCESSORIES

- MULTI-PURPOSE BLADE KIT
- CLAM SHELL KIT
- SERRATED SIDE PLATE KIT
- RUBBER PROTECTION KIT
- ELECTRICAL KIT FOR 2 LINE FUCTIONALITY
- 24 MONTH WARRANTY

SPECIFICATIONS

RECOMMENDED EXCAVATOR	≥ 3 ≤ 6 ton
WEIGHT	288 kg / 0,288 ton
CAPACITY (CLAWS CLOSED)	0,10 m3 / 100 L
ROTATION	360° Gradi
OIL PRESSURE (ROTATION)	> 150 PSI
OIL FLOW RATE (ROTATION)	10 I/min.
OIL PRESSURE (OPENING/CLOSING)	0 - 250 PSI
OIL FLOW RATE (OPENING/CLOSING)	40 I/min.
SIZE A	1300 mm
SIZE B	475 mm
SIZE C	865 mm
SIZE D	425 mm
SIZE E	770 mm
SIZE F	960 mm
SIZE G	520 mm

APPLICATION AREAS

















FOREST MAINTENANCE



TUNNELS AND ENCLOSED SPACES

PIPELINES

URBAN CONSTRUCTION SITES

MAINTAINING LANDSCAPE AND AGRICULTURAL AREAS









