



COMMAQUINAS TRAILER PRICE QUOTATION

Attention to :	Offer No: TN140922-2
Company Name :	Date: 19.07.2022
Company Address:	Sent by : Commaquinas
E-mail:	Number of pages : 4
Phone:	Phone: +351 933 266 003

TECHNICAL CONDITIONS:

39 M3 V Type Bulker Semi Trailer Technical Specifications Structure:

Tank is "V" shape and discharging is from bottom. Tank is build ST quality 5 mm thickness.. Working pressure 2 bar and test pressure 3 bar. 2 unit air pressure manometer. 4 " discharging system and 6+6 mt special alloy discharge hose and 1 unit regulated to 2.5 bar safety valve and Upper catwalk

Valves are ball valve

Steel Discharging pipe will be 4" on the left side of the tanker





2' diameter air supply hose from aboveAccess ladder is set to trailer.3 pcs of 450 mm manhole cover for loading 1Pcs Unloading dischage Cones





Air Compressor:

2 Head New Chinese Diesel Engine air compressor made Betonsan Brand with Flowrate 10.200 Lt/min capacity

Axles: 3x12 tones **BPW type** Pırlanta Brand Turkish Brand Axle, Drum brake There are brake shoes and heavy brake levers suitable for EU norms

First axle liftable



Suspensions; It is supplied with Turkish Brand of 6 pcs of air spring suspension

Brake System; Wabco or Knoor EBS Brake system 1 Axles with T 30/30 emergency brake chamber, 2 axles with T 30 service brake chambers

Electrical system; ADR suitable Sa-ba or Sertplas brand 2x7 pin sockets - 24V, lights accord to standard in SAE rear stop lamps, side marker lamps, brake safety warning lamps and signal light fitted at the rear

2 tail & stop combined lamps (red)

2 turn signal combined lamps (orange) 1 license lamp (white)





Tires; 6 Pieces 385 65 R 22,5 European Brand

Rims; 6 Pieces 22.5 Jantsa-Jantas Brand suitable for Intradisc

King Pin; Jost Type Turkish brand DIN 74080 standards 2" king pin detachable from below made by SAE standards 8 bolt type. With E certificate. Fifth Wheel heigt is; 1250 - 1330 mm

Landing Legs; Jost Type Turkish brand Front Jack feet are telescopic, parallel working, double speed jointed with wide shoes static 50 tons, dynamic 25 tons capacity

Painting:

After the construction process, all trailers are sand blasted

Before the painting, all parts are cleaned carefully

Epoxy gray is used for first protecting primer coating as 50 micron

2 Times of high quality paints applied on complete trailer

The color of trailer is selected by customer requested according to RAL codes

Painting thickness to be 100 micron, and all painting process to be submitted with certifications

Accessories:

Water Tank

Spare tyre carrier (spare tire carrier will be place up to bottom discharging point)

Wheel leaning mounting

Fire extinguisher

Preserving cabinet.

Tool Box

Access Ladder

Cat Walking manually operated

Plastic Mudguards

COMMERCIAL:

Quantity(unit) :1 Psc 3 Axle VType 39 m3 Cement Tanker Semi Trailer

Price : 39.000,0 Euros CIF inclued certificate CE

Payment Term : %35 down payment with the order, %65 Balance before shipment

Shipment terms : all custom process will be arranged in Turkey by us

Delivery Time :1 Unit trailer will be ready in 30 days

Warranty : The Trailers will be guaranteed for 12 months from the installation





Document : Commercial invoice, packing list, bill of lading, Certificate of origin, for

additional documents please do not forget to ask before the shipment time.

Export documents : Expenses regarding the export documents is included in the price











